

NORA Class Specs- 2009 Dirt Oval

Losi 1/10th scale Slider Sprint car

This rule package outlines all the requirements for a controlled racing program (SPEC) for the Losi 1/10 Slider. The rules set forth are a simple guideline to promote entry level racing without increased cost for the racer.

Vehicle Requirements: Losi 1/10 Slider must be run in stock configuration or better known as BOX STOCK. No aftermarket components can be added to the vehicle to enhance handling capabilities.

The only items that can be changed are as follows:

- **Gearing:** Both Pinion and Spur may be changed. LOSB 3548 Steel idler gear can be used in transmission.
- **Tires:** Only Losi 1/10 Slider tires can be used. The vehicle is stock with a standard compound tires. A harder compound tire can be used for the front (LOS7432) and rear (LOS7462) of the vehicle. The stock "orange" colored foam MUST be used in all tires. No tire additives allowed
- **Body:** Colors and paint schemes can be changed.
- Racers must use headers, roll bars, and nerf bars to keep scale look of vehicle. Racers can upgrade to chrome plated roll cage if desired
- Rear wing position can be within standard range of adjusted for improved handling.
- Front and rear wing must be used at all times.
- Driver's helmet can be removed or holes can be added to aid in cooling the esc.
- **Suspension:** Wheel Base can be adjusted by rear hubs and spacers only
- Shock oil viscosity
- Different length camber link locations can be used to improve performance.

Motor: For the 1/10 Slider Spec class the stock Losi LM-32K motor must be used at all times.

Battery: 6 cell 7.2 volt NiMH 5000 mah or less, Li-po 2S 7.4 volt 5400 mah or less.

Electronics: Vehicle must use all stock Losi electronics that are supplied with the vehicle except as noted below. They are as follows:

- **ESC:** Both New and old ESC's that came with kits/ Exception: can also use Dynamite Tazer 15T
- **Radio:** LOSB0805 LSR-3000 DSM Transmitter
- **Receiver:** LOSB0806 MRX-3000 DSM Receiver
- **Servo:** LOSB0818 MSX-Digital Servo

Vehicle Minimum Weight: 4 lb. 5 oz. (69 ounces) which is the stock weight of vehicle with Losi 3600NiMh Performance Spec battery.